

Safety Data Sheet SolSafe® 245

1. Identification

PRODUCT IDENTIFIER

Product Identity SolSafe 245

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company Name BioChem Systems, Inc.
P.O Box 8098
The Woodlands, TX 77387-8098

Contact information 800-777-7870

EMERGENCY TELEPHONE NUMBER PERS: (800) 633-8253

2. Hazard(s) Identification

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Combustible Liquid;H227 Combustible Liquid.
Asp. Tox. 1;H304 May be fatal if swallowed and enters airways.

LABEL ELEMENTS

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

Safety Data Sheet

SolSafe® 245

[Storage]:

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/Information on Ingredients

MIXTURE

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Hydrotreated petroleum distillates CAS Number: Proprietary	50 - 75	Asp. Tox. 1;H304	[1]
(2-methoxymethylethoxy)propanol CAS Number: Proprietary	25 - 50	Not Classified	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First Aid Measures

DESCRIPTION OF FIRST AID MEASURES

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Overview	Primary routes of entry: eyes, skin Effect of acute and chronic overexposure: Acute: Eyes: Liquid causes eye irritation. Skin: Prolonged contact, as with clothing wetted with material, may cause more severe irritation and discomfort. May cause dermatitis and aggravate existing skin conditions. Respiratory System: High vapor concentration may cause headaches and irritation to the respiratory system.
-----------------	--

Safety Data Sheet

SolSafe® 245

Ingestion: May irritate stomach and intestines. If swallowed may be aspirated into lungs resulting in pulmonary edema and chemical pneumonitis. Ingestion may cause burns to the digestive tract. Chronic: Repeated skin contact may cause a persistent irritation or dermatitis.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation

May be fatal if swallowed and enters airways.

5. Fire-Fighting Measures

FLAMMABILITY

Flammability Flash Point: 145F (TCC)

EXTINGUISHING MEDIA

Dry chemical or foam.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

ADVICE FOR FIRE-FIGHTERS

Use self-contained breathing apparatus and full protective clothing (Bunker gear).

ERG Guide No. ----

6. Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Put on appropriate personal protective equipment (see section 8).

ENVIRONMENTAL PRECAUTIONS

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Safety Data Sheet SolSafe® 245

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

Avoid use of any ignition source near spill.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Handle containers carefully to prevent damage and spillage.

Store in a cool dry area, away from heat, sparks and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

Incompatible materials: Strong oxidizing agents and acids.

Store in original container in well ventilated areas at temperatures below 140F. Store in closed containers away from heat or sources of ignition and oxidizing materials. Protect against physical damage to containers.

See section 2 for further details. - [Storage]:

8. Exposure Controls and Personal Protection

CONTROL PARAMETERS

Exposure

CAS No.	Ingredient	Source	Value
Proprietary	(2-methoxymethylethoxy)propanol	OSHA	TWA 100 ppm (600 mg/m3) [skin]
		ACGIH	TWA: 100 ppm STEL: 150 ppm Skin
		NIOSH	TWA 100 ppm (600 mg/m3) ST 150 ppm (900 mg/m3) [skin]
		Supplier	No Established Limit
Proprietary	Hydrotreated petroleum distillates	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	Recommended 300 ppm PEL

Safety Data Sheet

SolSafe® 245

Carcinogen Data

This product contains no materials at levels which require reporting.

EXPOSURE CONTROLS

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Impervious gloves are recommended.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Ensure emergency eye wash and shower stations are available in workplace. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and Chemical Properties

Appearance	Colorless Liquid
Odor	Hydrocarbon
Odor threshold	Not Measured
pH	N/A
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	360F
Flash Point	145F (TCC)
Evaporation rate	>1 (H ₂ O=1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure	<1 mmHg @20C
Vapor Density	>1 (air=1)
Specific Gravity	0.8 @25C
Solubility in Water	Negligible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	<20.5
VOC Content	7.0 lbs/gal

Safety Data Sheet SolSafe® 245

10. Stability and Reactivity

REACTIVITY

Hazardous Polymerization will not occur.

CHEMICAL STABILITY

Stable under normal circumstances.

POSSIBILITY OF HAZARDOUS REACTIONS

No data available.

CONDITIONS TO AVOID

Excessive heat and open flame.

INCOMPATIBLE MATERIALS

Strong oxidizing agents and acids.

HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

11. Toxicological Information

ACUTE TOXICITY

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Hydrotreated petroleum distillates (Proprietary)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available	No data available	No data available
(2-methoxymethylethoxy)propanol - (Proprietary)	3,500.00, Rat - Category: 5	19,000.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable



Safety Data Sheet SolSafe® 245

Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

12. Ecological Information

TOXICITY

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Hydrotreated petroleum distillates (Proprietary)	45.00, Pimephales promelas	4,720.00, Dendronereides heteropoda	Not Available
(2-methoxymethylethoxy)propanol - (Proprietary)	10,000.00, Pimephales promelas	1,919.00, Daphnia magna	969.00 (72 hr), Algae

PERSISTENCE AND DEGRADABILITY

There is no data available on the preparation itself.

BIOACCUMULATIVE POTENTIAL

Not Measured

MOBILITY IN SOIL

No data available.

RESULTS OF PBT AND VPVB ASSESSMENT

This product contains no PBT/vPvB chemicals.

OTHER ADVERSE EFFECTS

No data available.

13. Disposal Considerations

Safety Data Sheet SolSafe® 245


WASTE TREATMENT METHODS

Observe all federal, state and local regulations when disposing of this substance.

14. Transport Information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN NUMBER	Not Applicable	Not Regulated	Not Regulated
UN PROPER SHIPPING NAME	Not Regulated	Not Regulated	Not Regulated
TRANSPORT HAZARD CLASS(ES)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
PACKING GROUP	Not Applicable	Not Applicable	Not Applicable
ENVIRONMENTAL HAZARDS			
IMDG	Marine Pollutant: No		
SPECIAL PRECAUTIONS FOR USER			
	No further information		

15. Regulatory Information

REGULATORY OVERVIEW	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
TOXIC SUBSTANCE CONTROL ACT (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS CLASSIFICATION	B3
NFPA/HMIS RANKINGS	

US EPA TIER II HAZARDS

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No



Safety Data Sheet SolSafe® 245

EPCRA 311/312 CHEMICALS AND RQS:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 EXTREMELY HAZARDOUS:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 TOXIC CHEMICALS:

(2-methoxymethylethoxy)propanol

PROPOSITION 65 - CARCINOGENS (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

PROPOSITION 65 - DEVELOPMENTAL TOXINS (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

PROPOSITION 65 - FEMALE REPRO TOXINS (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

PROPOSITION 65 - MALE REPRO TOXINS (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

NEW JERSEY RTK SUBSTANCES (>1%):

(2-methoxymethylethoxy)propanol

PENNSYLVANIA RTK SUBSTANCES (>1%):

(2-methoxymethylethoxy)propanol

16. Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

The information contained in the above SDS is intended for the exclusive use of BioChem Systems, Inc. The above data have been compiled primarily from the SDS supplied to BioChem Systems, Inc. by the manufacturer and/or supplier. While the information is believed to be pertinent and current, no warranty expressed or implied is given as to its accuracy. This SDS is to be used as a guideline for safe work practices and emergency response. Any questions regarding the safe use of this material not outlined above should be directed to the BioChem Systems, Inc. Technical Services Department.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

End of Document