

Clear Track, 900 μm Clear Fiber 900 μm Clear Fibre, 1 km spool

CORNING

Part Number:
80611498058

The pathway captures and routes a single 900 μm Clear Fiber to the desired outlet or terminal location, while remaining virtually invisible. Installation is simple – no heat, fluid adhesives, or staples – and the track can be installed on many surfaces, including latex and oil paints and wallpaper.



Clear Track, 900 μm Clear Fibre, 1 km spool

Clear Track, 900 µm Clear Fiber 900 µm Clear Fibre, 1 km spool

CORNING

Specifications

General Specifications

Environment	Indoor
Fibre category	G.657.B3/G.652.D
Application	General purpose
Cable geometry	Round

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fibre name	900 µm Clear Fibre
Fibre compliance	ITU-T G.652.D and ITU-T G.657.B3
Cladding diameter	125 µm ± 0.4µm
Mode-Field Diameter at 1310 nm	8.7 µm ± 0.5µm
Mode-Field Diameter at 1550 nm	9.65 µm ± 0.7µm
Coating diameter	242 µm

Dimensions

Cable Weight	1.62 kg/km
Max. cable length per reel/drum	1000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea